



**Cassara**  
LIGHTING



## LED UFO HIGHBAY



### 150W LED UFO SPECIFICATION

**S/CAS-HB-150W-5K**

Luminaire Wattage	150W
Effective Luminous Flux	24 000 Lumens
Efficacy	160 lm/W
Correlated Colour Temperature (CCT)	5000K
Colour Rendering Index (CRI)	+80
<b>Beam Angle</b>	<b>90° Standard*</b>
Power Factor	0.92
Input Voltage	220-240 Vac,50/60Hz
<b>Surge Protection</b>	<b>10kV</b>
Operating Temperature	-30°C to + 50°C
IP Rating	65
<b>Lifespan of LED @Ta=25°C (hours)</b>	<b>L80B10-73000 Hours</b>
Warranty	5 Years
Materials & Finish	Aluminum Alloy I Polycarbonate Optical Lens Black Powder Coating (RAL9017)
Gross Weight	2.2kg
Certification	CE, RoHs, CB. SAA and C-Tick
Mounting type	Suspension/Ceiling Mount

### 200W LED UFO SPECIFICATION

**S/CAS-HB-200W-5K**

Luminaire Wattage	200W
Effective Luminous Flux	32 000 Lumens
Efficacy	160 lm/W
Correlated Colour Temperature (CCT)	5000K
Colour Rendering Index (CRI)	+80
<b>Beam Angle</b>	<b>90° Standard*</b>
Power Factor	0.92
Input Voltage	220-240 Vac,50/60Hz
<b>Surge Protection</b>	<b>10kV</b>
Operating Temperature	-30°C to + 50C
IP Rating	65
<b>Lifespan of LED @Ta=25°C (hours)</b>	<b>L80B10-73000 Hours</b>
Warranty	5 Years
Materials & Finish	Aluminium Alloy I Polycarbonate Optical Lens Black Powder Coating (RAL9017)
Gross Weight	2.9kg
Certification	CE, RoHs, CB. SAA and C-Tick
Mounting type	Suspension/Ceiling Mount

**\*Note: 60° or 120° lenses available on request.**